

6005BA

schoen + sandt

schoen + sandt machinery GmbH

Hydraulic Die Cutter **Type 6005BA**

Your Benefits

- *Mechanical synchronized speed for parallel cutting even under off-center load*
- *Automatic adjustment of cutting die height*
- *PLC with touch panel and clear text error indication*
- *Remote maintenance via telephone modem*
- *Automated, motor driven low point limitation with electrical switch off in end position*



More than 150 years
of perfect solutions
www.schoen-sandt.com

Hydraulic Die Cutter

Type 6005BA

Technical specification

- Welded steel construction with 4 columns and receding beam
 - With mechanical synchronization for maintaining plane-parallelism between beam and base
 - Without central lubrication, with self-lubricating bushings
 - The beam travel is powered by an electric motor
 - The beam return travel distance is infinitely variable
 - The oil-tight welded hydraulic power unit is installed at the rear side of the cutting machine
 - The electric control cabinet is mounted to one side of the machine
- The operator's panel and all electric operating and control elements are arranged on the front side of the control cabinet
- A "Siemens S7" PLC controls the various movements
 - Trilingual operator's guidance via clear text error display
 - Preselect stroke counter
 - Total stroke counter
 - Automatic adjustment to the cutting die height
 - Safety light curtain for protection and cutting stroke release
 - Cutting stroke release selective via 1-cycle resp. 2-cycle operation or via a push button
 - Protective guarding in accordance with the European Standards
 - Modem for quick response, long distance technical diagnosis and remote maintenance
 - 4 mechanical low point limits, automatically adjustable, adjusting accuracy 0,05 mm
 - New differential hydraulic

Specification

Daylight in mm	185	
Working stroke, max. in mm	160	
Table Height in mm	950	
Type	6005BA/160.85/70	6005BA/206.105/125
Cutting force in kN (Mp)	700 (70)	1250 (125)
Cutting area in mm	1600 x 850	2060 x 1050
Motor drive in kW	5,5	11
Oil requirement in ltr	200	300

Other available sizes:

2200 mm x 1100 mm / 1000 kN
 2060 mm x 1050 mm / 1250 kN
 2060 mm x 1250 mm / 1250 kN

Subject to technical modifications.