

Hydraulic Traveling Head Cutting Press

Model 7072C

- The movement of travelling head is controlled by two-hand and an automatic travelling switch to make operation easy.
- Two-hand operation and no continuous cutting are designed for security.
- The structure of travelling head helps the operator to have good open view.
- The cutting stroke can be adjusted easily and quickly in accordance with the height of cutting dies.
- High capacity; low power consumption.
- The roller feeding system or rear material plate is available.



	7072C - 25	7072C - 40
Cutting Force	25 tons	40 tons
Hydraulic Motor Power	2HP	3HP
Positional Motor Power	1HP	1HP
Cutting Head (L x W)	500 x 500 mm	650 x 650 mm
Cutting Pad (L x W)	1600 x 500 mm	1750 x 650 mm
Stroke	5 – 120 mm	5 – 120 mm
Oil Filling	60 liters	80 liters
Net Weight	1555 kg.	2752 kg.
Gross Weight	(to be provided before shipment)	
Dimensions (L x W x H)	1950 x 1275 x 1990 mm	2275 x 1415 x 2190 mm
Packing Size (L x W x H)	2140 x 1000 x 2200 mm	2500 x 1250 x 2450 mm

American

Schoen
 MACHINERY COMPANY

100 Cummings Center, Suite 140A • Beverly, MA 01915 U.S.A.
 (t) 978-524-0168, 800-777-2762 (f) 978-524-4805, (e) info@asm-schoen.com